

International Cadet Class

Cadet Mark III Measurement Form 2009

SAIL / ISAF PLAQUE NUMBER.....

INTRODUCTION

This contains the form for use for certification or re-certification of Cadet Mark III hulls.

MEASUREMENT INSTRUCTIONS

The International Cadet Mark II may be built by any builder without a license from the ICA. Therefore, the purpose of measurement is to ensure so far as possible that all the relevant rules have been complied with and that hull fittings have been correctly placed.

When completed by the Measurer and with the builder's declaration, the Measurement Form should be forwarded by the Measurer to the MNA / National Association as appropriate. The Measurer must retain a copy for his own records and provide a copy to the builder or owner. The builder or owner may then apply to the MNA / National Association as appropriate with the current fee for the issue of a hull measurement certificate using the form on page 10 below.

CADET MARK III MEASUREMENT FORM 2009

Is the hull built out of timber (either solid or plywood)? (rule D.1.9)	Yes / No
Are the requirements of the Wooden Boat Supplement (rule H.1) complied with?	Yes / No

Measurements	Min. mm	Port	Actual	Starbd	Max. mm
Datum Line B to Keel at Section 3, 2134mm from Datum Plane A.	-	-	76	-	-
Datum Line B to Keel at Section 8, 610mm from Datum Plane A	-	-	140	-	-
Notes: (i) Measure Datum Line B to Hull Datum Point and to Datum Line C at centreline at fore transom so that a line parallel to Datum Line B can be established above the decks. (ii) Leave marks at sections for beam at Chine and beam at deck level.					
Datum Plane A to the point of intersection on the centreline of the extension of the outer surface of the fore transom with the extension of the lower surface of the keel (ignoring any permitted rounding).	3067	-		-	3117
Datum Line B to Keel at fore transom	331	-		-	361
Datum Plane B to chine at fore transom	359				383
Datum Plane B to Datum Line C at fore transom	680				707
Datum Line B to Keel at Section 1, 2743mm from Datum Plane A	184	-		-	208
Datum Plane B to Chine at Section 1	255				281
Datum Plane B to Datum Line C at Section 1	623				661
Datum Line B to Keel at Section 2, 2438mm from Datum Plane A	109	-		-	133
Datum Plane B to Chine at Section 2	207				231
Datum Plane B to Datum Line C at Section 2	599				633
Datum Plane B to Chine at Section 3, 2134mm from Datum Plane A	207				231
Datum Plane B to Datum Line C at Section 3	575				599
Datum Line B to Keel at Section 4, 1829mm from Datum Plane A	48	-		-	72
Datum Plane B to Chine at Section 4	184				204
Datum Plane B to Datum Line C at Section 4	547				577
Datum Line B to Keel at Section 5, 1524mm from Datum Plane A	58	-		-	75
Datum Plane B to Chine at Section 5	195				211
Datum Plane B to Datum Line C at Section 5	528				558
Datum Line B to Keel at Section 6, 1219mm from Datum Plane A	71	-		-	95
Datum Plane B to Chine at Section 6	210				234
Datum Plane B to Datum Line C at Section 6	512				542
Datum Line B to Keel at Section 7, 914mm from Datum Plane A	96	-		-	90
Datum Plane B to Chine at Section 7	229				253
Datum Plane B to Datum Line C at Section 7	503				533
Datum Plane B to Chine at Section 8, 610mm from Datum Plane A	263				279
Datum Plane B to Datum Line C at Section 8	502				526
Datum Line B to Keel at Section 9, 305mm from Datum Plane A	166	-		-	190
Datum Plane B to Chine at Section 9	284				310
Datum Plane B to Datum Line C at Section 9	493				523
Datum Plane B to Keel at aft transom	202				224

Datum Plane B to Chine at aft transom	306				328
Datum Plane B to Datum Line C at aft transom	490				520
Beam of fore transom at Chine	152	-		-	168
Beam at Chine at Section 1	520	-		-	574
Beam at Chine at Section 2	765	-		-	796
Beam at Chine at Section 3	928	-		-	952
Beam at Chine at Section 4	1020	-		-	1050
Beam at Chine at Section 5	1080	-		-	1104
Beam at Chine at Section 6	1084	-		-	1114
Beam at Chine at Section 7	1058	-		-	1088
Beam at Chine at Section 8	1004	-		-	1028
Beam at Chine at Section 9	931	-		-	961
Beam at Chine at aft transom	839	-		-	863
Datum Plane A to the aft edge of the keel where it joins the aft transom	46	-		-	56
Datum Plane A to forward end of the daggerboard slot	1835	-		-	1885
Datum Plane A to aft end of daggerboard slot	1518	-		-	1568
Datum Plane A to forward end of skeg	965	-		-	1005
Depth of skeg near aft end (including keelband to the lowest point on the keelband)	76	-		-	-
Width of skeg, upper surface in contact with keel at aft end	38	-		-	-
Width of skeg, upper surface in contact with keel at forward end	20	-		-	-
Width of the flat part of the lower surface of the skeg (measured as if it was not rounded where there is permitted rounding)	19	-		-	-
Radius at aft end of skeg	20	-		-	30
Save for permitted rounding within 4mm of where the Planes meet, are the side and bottom surfaces of skeg flat (surfaces 2mm or less from 300mm straight edge)?	✓ or ✗				
Is the radius where the skeg meets the keel \leq 6mm?	✓ or ✗				
Height of daggerboard case measured midway between fore and aft ends	290	-		-	-
Is the internal width of the daggerboard case the same as the width of the slot in the keel?	✓ or ✗				
Are the sides of the slot parallel save for permitted rounding within 9mm of each end?	✓ or ✗				
If fitted, are any additional strips of non-metallic material fitted in the slot within 30mm of the top and bottom of the slot with uniform width of opening?	✓ or ✗ or "not fitted"				
If fitted are additional strips of non-metallic material fitted within 30mm of each end of the slot at the top and bottom to act as positioning and protection of the daggerboard?	✓ or ✗ or "not fitted"				
Internal width of daggerboard case (excluding permitted additional material)	15	-		-	-
Is the keel continuous from fore transom to aft transom?	✓ or ✗				
Save for permitted rounding, is the lower surface of the keel flat athwartships (surface less than 2mm from 300mm straight edge)?	✓ or ✗				
Save for permitted rounding, are the sides of the keel flat (surface less than 2mm from 300mm straight edge)?	✓ or ✗				
Are the flat sides of the keel at $90^\circ \pm 5^\circ$ to the flat part of the lower surface of the keel?	✓ or ✗				
Save for permitted rounding and radiussing, does the keel vary in thickness throughout its length by more than 5mm? (✓ = "no")	✓ or ✗				

Save for permitted rounding, are the aft ends of the keel and skeg so flat and so in line with the outer face of the aft transom that a straight edge placed anywhere on such surfaces within 200mm of the point where the keel joins the transom is nowhere (save at the permitted rounded parts) more than 2mm from such surfaces?	✓ or ✗				
Save for permitted rounding, is the fore end of the keel so flat and so in line with the outer face the fore transom that a straight edge placed anywhere on such surfaces within 200mm of the point where the keel joins the transom is nowhere (save at the permitted rounded parts) more than 2mm from such surfaces?	✓ or ✗				
Width of keel throughout length (measured between its flat surfaces)	76	-		-	-
Thickness of keel throughout length	11	-		-	-
Radius at fore end of keel	20	-		-	30
Radius at edges of keel throughout its length	-	-		-	10
Radius where bottom panels meet keel					6
Radius where skeg meets keel	-	-		-	6
Is a straight edge 300mm long placed athwartships anywhere on the outer surfaces of the side or bottom panels (save (i) within 4mm of the edges of such panels and (ii) within 40mm of Datum Line "C") anywhere more than 3mm from the hull surface? (✓ = "no")	✓ or ✗				
Is a straight edge 300mm long placed anywhere on the outer surfaces of the bow or aft transoms (save (i) within 4mm of their edges and (ii) within 40mm of Datum Line "C") anywhere more than 3mm from such surfaces? (✓ = "no")	✓ or ✗				
Except where otherwise specifically permitted, does any rounding on the chines or intersection of Planes on the outside of the hull beyond 4mm from the point of intersection of the two adjacent Planes? (✓ = "no")	✓ or ✗				
Chine angle at Section 3	114°		-		122°
Chine angle at Section 8	114°		-		122°
Are rubbing bands of brass, light alloy or plastic fitted?	✓ or ✗				
Are rubbing bands of convex or flat section strip?	✓ or ✗				
Minimum cross-section dimension 10mm by 2mm?	✓ or ✗				
Do bands run the full length of the keel and skeg (except in the way of any self-bailer in the keel), and are they double for the full length of the daggerboard slot?	✓ or ✗				
Are the Chine bands a minimum length of 1219mm each, positioned a minimum of 600mm from the aft transom?	✓ or ✗				
Panel thickness (including any g.r.p., epoxy, filler paint and varnish finishing)	✓ or ✗				20

Measurements	Min. mm	Actual mm	Max. mm
Hull Datum Point to Datum Line C at fore transom on centreline (measured in a straight line between the two points and not necessarily parallel to Datum Line B)	3201		3251
Hull Datum Point above the straight line joining Datum Line C at the aft transom on one side of the boat with Datum Line C at the aft transom on the opposite side of the boat	0		50
Datum Line C on the centreline at the fore transom above the straight line joining Datum Line "C" at the fore transom on one side of the boat with Datum Line "C" at the fore transom on the opposite side of the boat	0		30
Beam at Datum Line C at fore transom	320		340

Beam at Datum Line C at Section 1	743		783
Beam at Datum Line C at Section 2	966		1006
Beam at Datum Line C at Section 3	1125		1155
Beam at Datum Line C at Section 4	1207		1247
Beam at Datum Line C at Section 5	1245		1285
Beam at Datum Line C at Section 6	1232		1272
Beam at Datum Line C at Section 7	1194		1234
Beam at Datum Line C at Section 8	1125		1155
Beam at Datum Line C at Section 9	1029		1069
Beam at Datum Line C at Aft Transom	934		958
Is a thwart made of wood or g.r.p. fitted which extends the full width of the boat?	✓ or ✗		
Width of thwart	102		-
Distance of aft edge of thwart forward of Datum Plane A	1416		1470
Optional aft extension of thwart maximum dimensions 250mm (athwartships) by 75mm (fore and aft) on the centreline	✓ or ✗	/	
Is thwart attached to or part of daggerboard case or capping?	✓ or ✗		
Inspection hole in each buoyancy compartment 90 – 160mm internal diameter?	✓ or ✗		
Drainage holes in buoyancy compartments (if fitted) 15 – 25mm internal diameter?	✓ or ✗		
Datum Plane A to aft side of forward bulkhead	2114		2170
Datum Plane A to forward surface of aft bulkhead	600		629
Are the external surfaces of the forward and aft bulkheads so flat that a straight edge 300mm long placed anywhere on them (save within 4mm of their upper edges where they may be rounded) is nowhere more than 3mm from the surfaces?	✓ or ✗		
Do the fore deck and aft deck extend to but not beyond the edges of the fore and aft bulkheads respectively?	✓ or ✗		
Does the side deck structure comply with the diagrams A and B on Measurement Plan No.5?	✓ or ✗		
At any point between 650 mm and 2100 mm forward of Datum Plane “A”, is the horizontal width of the side deck structure, including the rubbing bead, measured to a point 25 mm below the top of the deck surface between 210 mm and 240 mm.?	✓ or ✗		
Do the deck surfaces in any transverse section not fall below Datum Line “C” nor rise more than 25 mm above it?	✓ or ✗		
Are there finger grips or grab slots on each side tank at least 20mm deep extending along the length of the sidedeck at least between 750mm and 2100mm from Datum plane A?	✓ or ✗		
Is the upper surface of the fore deck at the centreline at the aft edge of the forward bulkhead above and not more than 46mm above the straight line from Datum Line “C” on one side of the boat to Datum Line “C” on the opposite side of the boat at that athwartships section?	✓ or ✗		
Is the upper surface of the aft deck at the centreline at the forward edge of the aft bulkhead above and not more than 50 mm above the straight line from Datum Line “C” on one side of the boat to Datum Line “C” on the opposite side of the boat at that athwartships section?	✓ or ✗		
Is a straight edge 300 mm long placed anywhere on the upper surfaces of the fore or aft decks parallel with the centerline and inside Datum Line “C” (save within 4mm of the aft edge of the foredeck and within 4mm of the fore edge of the aft deck where those decks may be rounded) anywhere more than 3mm from the surfaces? (“no” = ✓)	✓ or ✗		
Is a string pulled taut across any athwartships section of the upper surfaces of the fore or aft decks anywhere more than 3mm away from those surfaces? (“no” = ✓)	✓ or ✗		

Is the buoyancy provided by at least two separate watertight compartments?	✓ or ✗	
Has buoyancy been added using a false or double bottom?	✓ or ✗	
Are the buoyancy compartments constructed by the full width forward and aft bulkheads and the fore and aft decks	✓ or ✗	
Is one inspection hole of circular shape of minimum diameter (including fixed part of inspection hole fitting) 90mm and maximum diameter (including fixed part of inspection hole fitting) 150mm provided in each buoyancy compartment? (Note: a second inspection hole of the same shape and minimum and maximum dimensions may be fitted in the fore and aft bulkheads)	✓ or ✗	
Is each inspection hole and drain hole provided with a suitable detachable cover or stopper capable of resisting accidental dislodgement by any means?	✓ or ✗	
Are there rubbing beads made of g.r.p., plastic or wood?	✓ or ✗	
At the edge of the decks from fore transom to aft transom do the rubbing beads have a depth measured along Datum Plane "E" of between 18mm and 25mm?	✓ or ✗	
At the edge of the decks from fore transom to aft transom do the rubbing beads extend for a minimum of 8mm and a maximum of 50mm from Datum Line "C" measured perpendicular to Datum Plane "E" at the points on Datum Line "C" from which the measurements are taken (save that within 25mm of the fore and aft transoms they may be tapered or rounded down to 0mm)?	✓ or ✗	
Are splash or spray guards provided, fitted to the foredeck, one each side of and joined at the centreline and running at least to Datum Line "C"?	✓ or ✗	
Are the guards made of wood?	✓ or ✗	
Is the minimum length of each guard 840 mm, with minimum height above the deck at the centre line 38 mm and tapering in a straight line to a minimum height of 19mm above deck at 840mm from their joint at the centreline?	✓ or ✗	
Does the section through the guards shall have a minimum base width of 12 mm, and a minimum radius to the top edge of 3 mm?	✓ or ✗	
Weight of hull including correctors	54kg	-
Weight of correctors		3kg
Does fore and aft centre of gravity conform to class rule D.10.3(c)?	✓ or ✗	
Does vertical centre of gravity conform to class rule D.10.3(b)? (plumb max. of 340mm)	✓ or ✗	
Is an ISAF plaque permanently placed on the inside of the aft bulkhead?	✓ or ✗	
Is the sail number of the boat permanently marked in contrasting colour (carved or engraved) on the port side of the outside of the aft transom in figures a minimum of 25mm in height?	✓ or ✗	

FITTINGS

Items	✓ or ✗
Mast step block containing a 29 ± 1 mm x 29 ± 1 mm square socket	
Upper face of mast step block (including protective plate, if fitted) not more than 46mm above the straight lines joining Datum Line "C" on the port and starboard sides of the hull at the sections containing the block which are parallel with Datum Plane "A"	
Mast tenon socket, of a minimum depth of 13mm	
Max. height of the mast step block including the optional protective plate, 20mm	
Towing fitting made of stainless or galvanised steel strongly attached to the fore transom at least 230 mm below Datum Line "C" at the top of the fore transom	
Bow plate to attach the forestay and headsail fitted on the centreline at the bow	
Two hull shroud plates or U bolts fitted 1835 mm ±25 mm from datum Plane A (1838mm ±25 mm if measured along deck)	
Two headsail fairleads fitted so that the bearing surface of each fairlead is a maximum of 50 mm	

from Datum Line "C"	
Headsail sheet cam cleats (if fitted) inboard of the headsail sheet fairleads and placed a minimum of 1735 mm from "Datum Plane A" measured along the deck	
Separate halyard cleats for the mainsail and headsail halyards fixed on the forward bulkhead	
Eye(s) for the mainsheet fixed 254 mm ±10 mm either side of the boat centreline on the deck at the aft transom	
If fitted, single block ("A") for centre sheeting fixed centrally a minimum of 1368mm and a maximum of 1493mm forward of datum Plane "A"	
Gudgeons and/or pintles for the rudder fitted on the aft transom	
Retaining clip or device attached to the aft transom or to a fixed or loose pintle so as to prevent the rudder from becoming accidentally detached while in use.	
Toe straps fixed in the hull for the crew and helmsperson. They may be fixed or adjustable, positioned to suit. The toe strap webbing may be of optional length and width. The ends of the toe straps shall be attached to the hull or bulkheads in an appropriate manner. For this purpose and for the purpose of adjustment only ropes, fairleads, deckeyes, cleats, and appropriate pads, plates and fastenings may be used.	
Inspection hole fittings consisting of a part fixed to the hull and a detachable cover	
Shock cord fitted and fixed for retaining the daggerboard in the daggerboard case	
Kicking strap eye plate fitted on the centreline (may be combined with the mast plate)	
<i>Optional Fittings</i>	
Fairleads for the spinnaker sheets (when fitted) must be fitted between 690mm and 1120mm from datum Plane "A" measured along the deck	
One open cleat for the spinnaker sheet may be fitted on each side of the boat between 690mm and 1120mm from datum Plane "A" measured along the deck	
One additional cleat for the spinnaker brace/guy may be fitted on each side of the boat and may be incorporated with the open fairlead referred to in D.9.3(xi) or the shroud plates or U bolts or the shroud adjusting plates. The cleats shall not extend beyond the outside of the rubbing strake or bead or deck flange or overhang	
A maximum of two lacing hooks are permitted to hold the spinnaker halyard	
If a spinnaker halyard is fitted its tail after passing through the fairlead on the mast shall be led through no more than the following: (i) one cleat (which may incorporate a fairlead, which fairlead shall not count towards the number of fairleads next-mentioned); (ii) a maximum of two fairleads or single blocks. The cleat may be fitted in any position. No gearing of the spinnaker halyard is permitted.	
One open fairlead may be fitted one each side of the boat to fairlead the spinnaker guys. It shall not project beyond the gunwale.	
Lifting handles are optional, but if fitted, four handles made of suitable material shall conform to the dimensions shown on Measurement Plan No.3 and shall be strongly fitted so that the centres of the aft pair of handles are 640mm ±50 mm from Datum Plane "A" and the centres of the forward pair of handles are 2370mm ±50 mm from Datum Plane "A"	
Maximum of two self-bailers	
It is permissible to have one or two open compartments or bags (for spinnaker or other loose gear), provided that they extend aft no more than 400mm from the forward bulkhead. The compartments or bags may be partly covered by flexible material which may be supported by shockcord. The bags may contain pockets and be supported by shockcord.	
Stowage clips, nets, ropes, bags and shockcord (and their fastenings) for paddle(s), spinnaker pole, sail bags and other loose equipment are permitted	
Drain hole fittings of internal dimensions 20 mm (± 5 mm) may be provided in each buoyancy compartment.	
One compass and mounting bracket only may be fitted (alternatively on mast)	
Mainsail Cunningham block, fairlead and cleat may be fitted (alternatively on mast)	
Such blocks cleats and fairleads as necessary for the operation of a spinnaker pole uphaul / downhaul system (alternatively on mast)	
A block, fairlead and cleat for the jib Cunningham may be fitted on the foredeck (alternatively on headsail)	
Blocks, fairleads and cleat for kicking strap system (alternatively as part of purchase system)	
Mechanical advantage of kicking strap system ≤ 6:1	

Shock cord may be fitted at or near the transom so as to prevent the mainsheet from catching on the corners of the transom	
Shock cord may be fitted to support the toe straps	
Such fastenings and ropes as may be appropriate in order to attach permitted fittings or equipment	
Are there any additional fittings?	

MEASURERS' REMARKS (if necessary continue on a separate sheet):

The Measurer has carried out and recorded the above measurements to the best of his ability, but makes no representations and gives no warranties as to their accuracy and is not to be held responsible for any inaccuracies. Responsibility for ensuring that the boat complies with the Class Rules lies wholly and exclusively on the builder and the owner. A measurement certificate may be withdrawn or cancelled if, amongst other things, it has been issued following an error, omission or mistake in the measurement process.

I certify that I have made the above outside hull, deck level and fittings measurements to the best of my ability and that they are within tolerances allowed.

Measurer's Name.....Signature:.....Date:.....

Status:.....

Address:.....

PLEASE USE BLOCK CAPITALS

BUILDER'S DECLARATION

On behalf of myself [and my Company], I hereby certify that this International Cadet, Sail Number.....
has been built in accordance with the class rules.

Name.....Signature.....Date.....

Builder's Name.....

Builder's Address.....

Date of Completion.....

The original Measurement Form when completed and with the builder's declaration should be forwarded by the Measurer to the MNA / National Association as appropriate. The Measurer must retain a copy for his own records and provide a copy to the builder or owner. The builder or owner may then apply to the MNA / National Association as appropriate with the current fee for the issue of a hull measurement certificate using the form on the next page.

International Cadet Class

REGISTRATION FORM

PLEASE USE BLOCK CAPITALS

1. Sail/ISAF Plaque Number.....
2. Boat name (if known).....
3. Builder.....
4. Measurer.....
5. Applicant's Name.....
6. Applicant's Address.....
.....
7. Club or Squadron (if known).....

I apply for a hull measurement certificate for the above boat and enclose the appropriate fee.

Signed.....

Dated.....

RESERVATION

The International Cadet Class reserves the right to refuse a Certificate of Measurement and to withdraw or cancel a Certificate already granted even in the case of a boat or boats which, although complying with the letter of the rules, if it has by reason of the exploitation of an error, omission or mistake in the rules, measurement plans or forms, in the opinion of the National or International Committee obtained a material superiority in competitive performance.