

▼ Shown: A-65, FZ-1625, HF-95Y, FZ-1634, FZ-1607, A-64, AM-21



The Genuine Range

Hydraulic Oil

Contents	Model Number	Use only genuine Enerpac Hydraulic Oil. The use of any other fluid will render your Enerpac warranty null and void.
1 litre	HF-95X	
5 litres	HF-95Y	
20 litres	HF-95T	

▼ OIL SPECIFICATION CHART

Viscosity Index	100 min
Viscosity at 210°F	42/45 S.U.S.
Viscosity at 100°F	150/165 S.U.S.
Viscosity at 0°F	<12,000 S.U.S.
API Gravity	31.0/33.0
Flash, C.O.C.°F	400
Pour Point, °F	-25
Aniline Point, °F	210/220
Paraffinic Base Colour	Blue

- Maximum pump volumetric efficiency
- Maximum internal heat transfer
- Prevents pump cavitation
- Additives prevent rust, oxidation and sludge
- High viscosity index
- Maximum film protective lubricity.

Manifolds

Description	Model Number	Dimensions (mm)
7-port Manifold, short	A-64	
7-port Manifold, short allows direct mounting of control valves to the manifold.	A-65	
6-port Manifold, hexagon Plugs furnished for all ports 3/8\"-18 NPTF.	A-66	
Control Manifolds For control of two or four single-acting cylinders simultaneously. AM-21 with 5 ports 3/8\"NPTF. AM-41 with 7 ports 3/8\"NPTF.	AM-21	
	AM-41	