


RFJ33-38 RECTANGLE FLAT-JACK DATASHEET



TECHNICAL DIMENSIONS



KEY FEATURES

- ✓ Ultra-Low Height Design (28-35mm)
- ✓ High Thrust Forces (40 - 360 Tonnes)
- ✓ Temporary or Permanent Suitable Use
- ✓ Full Proof-Load (UKAS) & ISO Traceable
- ✓ Circular, Square & Rectangular Models

APPLICATIONS

- Preloading Steelwork & Load-Transfer
- Excavation Struts & Temporary Props
- Settlement, Pre-Deflection & Jacking
- Bridge Bearing Replacement & Lifting
- Hydraulic to Permanent Transfusion

SPECIFICATIONS

Model: RFJ33-38

Maximum Capacity	1250 kNs
Maximum Stroke	25 mm
Maximum Pressure	140 Bar
Fluid Requirement	1.10 Litres
Jack Weight	10.00 Kgs
Type / Model	Rectangle Flat-Jack
Hydraulics	Single-Acting
Function	Water, Oil & Grout Types
Effective Area (approx.)	893 cm ²

KEY DIMENSIONS

Collapsed Height (C)	35 mm
Extended Height	60 mm
Outside Size (A)	330 x 380 mm
Thrust Plate Size (B)	285 x 335 mm

STANDARD SELECTION

